



User Experience Quality Analysis Method Based on Frequency Domain Characteristics of Physiological Signal

Ke Sun, Yuan An^(✉), Kailiang Zhang, and Ping Cui

Jiangsu Province Key Laboratory of Intelligent Industry Control Technology,
Xuzhou University of Technology, Xuzhou 221018, China
anyuan@xzit.edu.cn

Abstract. In recent years, the development of intelligent driving is rapid, the related business is constantly upgrading, and the end-user service is becoming more and more perfect. From the perspective of end users, obtaining the evaluation results of experience quality is an effective way to enhance the core competitiveness of business. In this paper, the mapping method of user experience quality is established based on the frequency domain characteristics of SEMG signal, so as to obtain the current real experience quality of intelligent driving terminal users. Data analysis shows that this method can effectively obtain the quality of real user experience. This study can be used as reference data to improve the business experience of intelligent driving terminal users, improve the relevant technical parameters, and enhance the core competitiveness.

Keywords: Physiological signals · Frequency · Domain characteristics · QoE

1 Introduction

As a research hotspot in the field of intelligent transportation, vehicle network is a typical application of Internet of things technology in the field of transportation system [1, 2]. It is the only way for mobile Internet and Internet of things to develop into business essence and depth [3]. The Intelligent driving refers to the car and the car, car and road, cars and people, cars and sensing devices [4], such as interaction, realize vehicle dynamic system for mobile communications network communication with the public, including car and car, car and road, and sensing equipment through the established sensing technology and network communication technology for vehicle [5], road and environment information, and between cars and people, namely the human-computer interaction [6], how to realize the seamless docking is key to the current research [7, 8]. In the vehicle network environment, the quality of all sensor technology and network communication technology is measured by the experience quality of the driving user [9–11].

Emotion recognition is a research hotspot in artificial intelligence [12], human-computer interaction, pattern recognition and digital signal processing [13], as well as

an important branch of emotion based computing [14]. In 1997, professor Picard of MIT media lab proposed that affective computing is one of the research methods for emotion [15]. Its purpose is to build a harmonious human-computer environment by giving computers the ability to recognize, understand, express and adapt to human emotions, and to make computers have higher and comprehensive intelligence. With the development of science and technology, people have higher and higher requirements for artificial intelligence, and how to make seamless communication between people and computers is also getting more and more attention [16–18]. As the basis of communication, emotion plays a more and more important role in human-computer interaction. Facial expression and voice emotion recognition systems will mature, however, both of these are non-physiological signals that do not directly reflect the inner psychological state of humans [18, 19]. Physiological signals (EMG, ECG, EGG) can more directly express people's current emotions. For example, EMG signal analysis can be used to judge the mental stress level and muscle fatigue state [20–24].

In the vehicle-net environment, the electromyographic signals of the driving user are easier to detect and can reflect the real experience quality of the driving user in real time. So this article uses the eight different emotional states (No emotion, Anger, Hate, Grief, Platonic love, Romantic love, Joy and Reverence) under electromyographic signal, and analyzes the relationship between their frequency characteristics and emotional state, in order to get through the electromyographic signal parameters to evaluate the quality of the vehicle under the network environment the user experience.

2 Related Work

Physiological signal refers to the signal spontaneously produced by human body in the physiological process, which contains a lot of information in human emotion and has great research significance. Physiological signals are regulated by the human nervous system and endocrine system, which can directly reflect the real emotions of human beings, and can greatly reduce the interference of other factors in the process of emotion recognition [25]. In the context of Intelligent driving, physiological signals change with the change of driving users' experience results of sensing technology and network communication technology, and the quality of user experience can be directly or indirectly reflected by the changes of human physiological signals [26]. By analyzing the relationship between driving user physiological signal characteristic parameters and user experience quality, we can regard the evaluation system as an open-loop system, taking human physiological signal changes as the input of the system and user experience quality as the output of the system [27]. The open-loop system can objectively represent the driving users' experience quality of various sensor technologies and network communication technologies of the Intelligent driving, so as to facilitate technicians to adjust relevant technical parameters in real time.

The electromyographic signal is the bioelectrical signal produced by the muscle activity and is the synthesis of the single action potential produced by the motor unit. SEMG signals are recorded from the skin surface and reflect the functional state of nerves and muscles. Because EMG signals can be recorded noninvasively, EMG signals have been used in a variety of fields, including motion analysis, neuromuscular system analysis, neuromuscular disease diagnosis, and prosthesis control. Because of SEMG signal

can overcome the problems existing in the subjective psychological evaluation, quantitative analysis of the working load and muscle function status and high correlation exists between the indexes and subjective fatigue, so its in human computer interaction and ergonomics application has a unique advantage, for the improvement of man-machine environment provides a more objective and effective theory basis [28, 29].

In terms of human-computer interaction, facial expression and speech emotion recognition system [30, 31] is relatively mature. However, these methods are non physiological signals, which can not directly reflect the internal psychological state of human beings. Compared with facial images and speech, physiological signals can express people's emotions more directly [32–34]. For example, GSR (galvanic skin reaction) can be used to analyze and judge people's psychological stress level [33]. As the sum of muscle motor potential, SEMG can quantitatively determine the internal load state of human body and evaluate the muscle stress state. Since SEMG signal can be obtained noninvasively, SEMG signal has been used in many fields, including motion analysis, muscle system analysis, muscle disease diagnosis and prosthesis control. SEMG signal has a relatively mature analysis method and acquisition technology, which is suitable for the evaluation of user's forelimb muscle state. In order to obtain the user's psychological and emotional state, determine the quality of user experience, and improve the human-computer interaction environment [27, 36].

Studies show that when the human body for a long time in a less or more excited emotional psychological state, the system remains tense muscles, it will produce a certain amount of load, the load build-up can cause muscle changes in physical properties of excitability and conductivity and reduced contractility, muscle physical exhibition staying power and flexibility is abate, the muscle will not be able to produce, the force needed for this phenomenon is called muscle fatigue. When fatigue occurs, the conduction velocity of muscle fibers decreases, and local muscles will produce such sensations as soreness, numbness and weakness. Therefore, it is an effective experimental method to extract surface EMG signals and find out the frequency characteristic parameters reflecting the change of conduction velocity [37, 38].

3 Assessment Process and Data Analysis

The end user experience quality evaluation process based on SEMG is shown in Fig. 1.

As shown in the figure, physiological comfort index includes human body pressure distribution data and EMG signal data. According to the data characteristics of physiological signal indicators and five levels of comfort evaluation level, the evaluation data set $K = \{k_1, k_2, \dots, k_n\}$ is defined by maximum value and minimum value method, As shown in formula (1):

$$z = \frac{\max(x) - \min(x)}{n} \quad (1)$$

Among them, $\max(x)$ and $\min(x)$ represent the maximum and minimum values of a class of physiological data, $n \sim x_{ij}$ values are graded, and $z \sim n$ values are the mean difference between the grades. In this paper, trapezoidal fuzzy method is used to reflect




Fig. 1. Assessment process.

the subjectivity of the end-users, and the correlation between the evaluation indexes and the evaluation data set is studied. As shown in formula (2).

$$\alpha_{ij} = \begin{cases} \frac{x - \alpha_{ij}^L}{\alpha_{ij}^{ML} - \alpha_{ij}^L}, & x \in (\alpha_{ij}^L, \alpha_{ij}^{ML}) \\ 1, & x \in (\alpha_{ij}^{ML}, \alpha_{ij}^{MR}) \\ \frac{x - \alpha_{ij}^R}{\alpha_{ij}^{MR} - \alpha_{ij}^R}, & x \in (\alpha_{ij}^{MR}, \alpha_{ij}^R) \\ 0, & x \in (-\infty, \alpha_{ij}^L) \cup (\alpha_{ij}^R, 0) \end{cases} \quad (2)$$

Among them, a_{ij} is the membership degree of the u_{ij} index to the evaluation set $K = \{k_1, k_2, \dots, k_n\}$, $\alpha_{ij}^L, \alpha_{ij}^{ML}, \alpha_{ij}^{MR}, \alpha_{ij}^R$ is the coordinate value of the trapezoidal membership function respectively, and there is $\alpha_{ij}^L < \alpha_{ij}^{ML} < \alpha_{ij}^{MR} < \alpha_{ij}^R$. If $\alpha_{ij}^L < \alpha_{ij}^{ML} = \alpha_{ij}^{MR} < \alpha_{ij}^R$, the trapezoidal membership function is transformed into a triangular membership function.

The experimental results show that the conduction velocity of muscle fibers is directly related to local muscle fatigue. Surface emg signals are extracted and converted into frequency characteristic parameters that can reflect the change of conduction velocity, thus reflecting the fatigue degree of muscles. These characteristic parameters are mainly obtained through time-domain and frequency-domain analysis.

In frequency domain analysis, the main analysis method is to conduct fast Fourier transform on EMG signal to obtain the spectrum or power spectrum of EMG signal, which can reflect the changes of EMG signal in different frequency components, so

it can better reflect the changes of EMG signal in frequency dimension. The spectral shift of SEMG signal power spectrum can be used as an experimental indicator of the conduction velocity of muscle fibers.

In order to quantitatively characterize the spectrum or Power spectrum of SEMG signals, researchers often use the following two indicators, namely Mean Power Frequency (MPF) and Median Frequency (MF).

The calculation method distribution of MPF value and MF value is as follows:

$$\text{MPF} = \frac{\int_0^{\infty} fP(f)df}{\int_0^{\infty} P(f)df} \quad (3)$$

$$\int_0^{\text{MF}} P(f)df = \int_{\text{MF}}^{\infty} P(f)df = \frac{1}{2} \int_0^{\infty} P(f)df \quad (4)$$

Where $P(f)$ is the EMG power spectrum.

Because the average power frequency is highly sensitive to the frequency spectrum variation under low load conditions, it can be used as the reliability measurement parameter of local muscle fatigue in human body. This experiment mainly detects the change of SEMG signal spectrum under different psychological and emotional states of users. There is no obvious muscle activity. However, due to the long-term load accumulation process, frequency-domain parameters are adopted for analysis.

4 The Experimental Results

In this paper, the emotional physiology database of MIT was used as the source data for processing and analysis. According to the data processing results, the upper extremity SEMG signals corresponding to different experience quality of users in the actual vehicle network environment under driving conditions were collected in subsequent studies.

The MIT emotion physiology database is 32 physiological data sets per day for 20 consecutive days. The DataSet I consists of four physiological signals and eight emotional state measurements. The experimenter sat in a quiet space at the same time every day and tried to experience eight emotional states under the guidance of the computer prompt system, and recorded the physiological signals of the experimenter in real time. The sampling frequency of all data was 20 Hz and the sampling time was 100 s. Participants were asked to experience eight emotional states: No emotion, Anger, Hate, Grief, Platonic love, Romantic love, Joy and Reverence.

The average power frequency (MPF) of SEMG signals in eight different emotional states of the subjects within 20 days was calculated and plotted as the corresponding histogram, as shown in Fig. 2. Since the experimental data are 2000 data of subjects in different emotional states, the duration of each emotion cannot be controlled absolutely, so the 2000 data in the data set may be intercepted at the beginning or end of the emotion. We took the average value of the 20-day measurement data and observed the mean value of MPF value of the experimenter's SEMG signal under different emotions, as shown in Fig. 3.




Fig. 2. Histogram of MPF value of SEMG signal in eight states.




Fig. 3. Mean MPF value of SEMG signal in 8 states within 20 days.

According to the results in Fig. 1 and Fig. 3, under Anger, Grief, Romantic love and Joy, SEMG signal MPF value had a larger amplitude, It indicates that the conduction velocity of muscle fibers is faster. The MPF value of SEMG signal was smaller under Platonic love, emotion and No emotion, and the results indicate that the conduction velocity of muscle fibers is slow.

Previous studies showed that the average power frequency MPF decreased with the gradual fatigue of muscles under static load. This experimental data for the subjects

did not appear under the muscle fatigue of acquisition, and no obvious passive fatigue phenomenon, thus the experimental results show that if the experimenter long-term at our Romantic love, Joy, Anger, Grief and four kinds of emotion, the muscular system will continue to be nervous, reduce muscle fiber conduction velocity and muscle fatigue state, the decrease of the quality of the user experience. If the subjects were in the three emotions of Platonic love, emotion and No emotion for a long time, the muscle system was relatively relaxed, and the excitability, conductivity and contractibility were less affected by the time dimension, which would not change significantly. The subjects were not prone to obvious fatigue, indicating that the user experience quality was good.

Figure 4 shows the spectrum of SEMG signals in eight emotional and psychological states of the subjects during the test on a certain day. The SEMG signal spectrum diagram showed that the frequency spectrum amplitude of the subject was larger in Anger and Romantic love, and the high and low frequency parts were significantly increased,




Fig. 4. SEMG spectrum diagram.

indicating that the muscle system of the subject was prone to fatigue in a certain period of time under these two emotions. Under emotion and No emotion, the amplitude of SEMG signal spectrum was small, and the distribution of high and low frequency was less, indicating that the muscle system of the subjects was not prone to fatigue in a certain period of time under these two emotions, and the quality of user experience was better than other psychological and emotional states.

Experiment found that the short-time Fourier transform of MPF, to some extent can well represent changes of muscle fatigue, but because of the Fourier transform is only applicable to smooth the mutations in the signal, so when change the SEMG signal, based on Fourier transform of frequency domain feature is not difficult to fully reflect the changes of muscle fatigue. Due to the experimental data for the subjects in the corresponding part of the SEMG signal with emotional state, likely in the mood or end the beginning of the end, there may be a jump, the results can only qualitative analysis to get the user psychological emotional state and there were some correlation between physiological signal characteristic parameters, can be used to get the user experience as a quality reference data. Later research can obtain corresponding user SEMG signals by changing various technical parameters in the Intelligent driving environment, and use more characteristic parameters to represent the user experience quality under different technical parameters, so as to provide guiding data for a more harmonious human-computer interaction environment.

5 Conclusion

In this paper, the mapping method of user experience quality is established based on the frequency domain characteristics of SEMG signal, so as to obtain the current real experience quality of intelligent driving terminal users. Data analysis shows that this method can effectively obtain the quality of real user experience. The relationship between MPF, the characteristic parameter of SEMG signal in frequency domain of No emotion, Anger, Hate, Grief, Platonic love, Romantic love, Joy and mood state of subjects was analyzed to provide reference data for judging the quality of user experience. The experimental results showed that in the state of Anger, Hate and other psychological mood swings, users had a large MPF amplitude and a large frequency spectrum in the low and high frequency bands, indicating that in this emotional state, the muscle system would be continuously tense, resulting in decreased muscle fiber conduction velocity, relatively easy muscle fatigue and decreased user experience quality. When users experience less disturbance of emotion such as agitation and No emotion, the muscle system is relatively relaxed, the excitability, conductivity and contractility are less affected by time dimension, and No significant change will occur. Users are not prone to obvious fatigue, indicating that the user experience quality is good.

The research results of this paper show that SEMG signals can be used as physiological signals to directly obtain user experience quality in the context of the Intelligent driving, and the characteristic parameters of user SEMG signals can be acquired in real time. The influence of technical parameters of the Intelligent driving on user experience quality can be analyzed, so as to create a more harmonious and integrated human-computer interaction environment.

Acknowledgements. This work is partly supported by Jiangsu technology project of Housing and Urban-Rural Development (No. 2018ZD265, No. 2019ZD039, No. 2019ZD040, No. 2019ZD041).

References

1. Jiang, D., Wang, Y., Lv, Z., et al.: Big data analysis-based network behavior insight of cellular networks for industry 4.0 applications. *IEEE Trans. Ind. Inf.* **16**(2), 1310–1320 (2020)
2. Jiang, D., Wang, Y., Lv, Z., et al.: Intelligent optimization-based reliable energy-efficient networking in cloud services for IIoT networks. *IEEE J. Selected Areas Communi.* (2019)
3. Jiang, D., Wang, Y., Lv, Z., et al.: A joint multi-criteria utility-based network selection approach for vehicle-to-infrastructure networking. *IEEE Trans. Intell. Transp. Syst.* **19**(10), 3305–3319 (2018)
4. Jiang, D., Huo, L., Song, H.: Rethinking behaviors and activities of base stations in mobile cellular networks based on big data analysis. *IEEE Trans. Netw. Sci. Eng.* **1**(1), 1–2 (2018)
5. Jiang, D., Wang, W., Shi, L., et al.: A compressive sensing-based approach to end-to-end network traffic reconstruction. *IEEE Trans. Netw. Sci. Eng.* **5**(3), 1–12 (2018)
6. Jiang, D., Huo, L., Li, Y.: Fine-granularity inference and estimations to network traffic for SDN. *PLoS ONE* **13**(5), 1–23 (2018)
7. Jiang, D., Zhang, P., Lv, Z., et al.: Energy-efficient multi-constraint routing algorithm with load balancing for smart city applications. *IEEE Internet Things J.* **3**(6), 1437–1447 (2016)
8. Jiang, D., Li, W., Lv, H.: An energy-efficient cooperative multicast routing in multi-hop wireless networks for smart medical applications. *Neurocomputing* **220**(2017), 160–169 (2017)
9. Wang, Y., Jiang, D., Huo, L., et al.: A new traffic prediction algorithm to software defined networking. *Mob. Netw. Appl.* (2019)
10. Qi, S., Jiang, D., Huo, L.: A prediction approach to end-to-end traffic in space information networks. *Mob. Netw. Appl.* (2019)
11. Wang, F., Jiang, D., Qi, S., et al.: A dynamic resource scheduling scheme in edge computing satellite networks. *Mob. Netw. Appl.* (2019)
12. Wang, F., Jiang, D., Qi, S.: An adaptive routing algorithm for integrated information networks. *China Commun.* **7**(1), 196–207 (2019)
13. Huo, L., Jiang, D., Qi, S., et al.: An AI-based adaptive cognitive modeling and measurement method of network traffic for EIS. *Mob. Netw. Appl.* (2019)
14. Huo, L., Jiang, D., Lv, Z., et al.: An intelligent optimization-based traffic information acquirement approach to software-defined networking. *Computat. Intell.* **36**, 1–21 (2019)
15. Huo, L., Jiang, D., Zhu, X., et al.: An SDN-based fine-grained measurement and modeling approach to vehicular communication network traffic. *Int. J. Commun. Syst.* **33**, 1–12 (2019)
16. Song, H.Y., Zhang, J.G., Wang, J., et al.: Study on muscle fatigue property of human body in shoulder loaded walking based on surface electromyogram. *J. Biomed. Eng.* **33**(3), 426–430 (2016)
17. Wu, Q., Chen, X., Ding, L., et al.: Classification of EMG signals by BFA-optimized GSVCM for diagnosis of fatigue statu. *IEEE Trans. Autom. Sci. Eng.* **14**(2), 915–930 (2017)
18. Liu, J., Zou, R.L., Zhang, D.H., et al.: Analysis of the muscle fatigue based on band spectrum entropy of multi-channel surface electromyography. *J. Biomed. Eng.* **33**(3), 431–435 (2016)
19. Wang, K.: Conventional time-frequency method of SEMG and strategy used for dynamic muscle fatigue analysis. *Chin. J. Sports Med.* **29**(1), 104–108 (2010)

20. Naeem, U.J., Xiong, C.H.: FFM: a muscle fatigue index extraction by utilizing fuzzy network and mean power frequency. *Int. J. Eng. Bus. Enterp. Appl.* **3**(1), 25–35 (2013)
21. Chowdhury, R., Reaz, B.M.L., Islam, M.T.: Wavelet transform to recognize muscle fatigue. In: *Proceedings of the 2012 Third Asian Himalayas International Conference on Internet*, pp. 1–5. IEEE, Piscataway (2012)
22. Li, Z., Wang, B., Yang, C., et al.: Boosting-based EMG patterns classification scheme for robustness enhancement. *IEEE J. Biomed. Health Inf.* **17**(3), 545–552 (2013)
23. Chen, L., Zhang, L.: spectral efficiency analysis for massive MIMO system under QoS constraint: an effective capacity perspective. *Mob. Netw. Appl.* (2020). <https://doi.org/10.1007/s11036-019-01414-4>
24. Chen, L., Jiang, D., Bao, R., Xiong, J., Liu, F., Bei, L.: MIMO Scheduling effectiveness analysis for bursty data service from view of QoE. *Chin. J. Electron.* **26**(5), 1079–1085 (2017)
25. Husić, J.B., Baraković, S., Muminović, S.: Is there any impact of human influence factors on quality of experience? In: *2017 40th International Convention on Information and Communication Technology, Electronics and Microelectronics (MIPRO), Opatija*, pp. 434–439 (2017)
26. De Moor, K., Arndt, S., Ammar, D., Voigt-Antons, J., Perkis, A., Heegaard, P.E.: Exploring diverse measures for evaluating QoE in the context of WebRTC. In: *2017 Ninth International Conference on Quality of Multimedia Experience (QoMEX), Erfurt*, pp. 1–3 (2017)
27. Alja'afreh, M., Al Maadeed, S., Alja'am, J.M., El Saddik, A.: Towards a comprehensive study of fatigue deducing techniques for evaluating the quality of experience of haptic-visual applications. In: *2020 IEEE International Conference on Informatics, IoT, and Enabling Technologies (ICIOT), Doha, Qatar*, pp. 339–344 (2020)
28. Fall, C.L., et al.: Wireless SEMG-based body-machine interface for assistive technology devices. *IEEE J. Biomed. Health Inf.* **21**(4), 967–977 (2017)
29. Zhang, M., Zhang, W., Zhang, B., Wang, Y., Li, G.: Feature selection of mime speech recognition using surface electromyography data. In: *2019 Chinese Automation Congress (CAC), Hangzhou, China*, pp. 3173–3178 (2019)
30. Hulliyah, K., Bakar, N.S.A.A., Ismail, A.R.: Emotion recognition and brain mapping for sentiment analysis: a review. In: *2017 Second International Conference on Informatics and Computing (ICIC), Jayapura*, pp. 1–5 (2017)
31. Tzirakis, P., Zhang, J., Schuller, B.W.: End-to-end speech emotion recognition using deep neural networks. In: *2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), Calgary, AB*, pp. 5089–5093 (2018)
32. Zhao, W., Zhao, Z., Li, C.: Discriminative-CCA promoted By EEG signals for physiological-based emotion recognition. In: *2018 First Asian Conference on Affective Computing and Intelligent Interaction (ACII Asia), Beijing*, pp. 1–6 (2018)
33. Chettupuzhakkaran, P., Sindhu, N.: Emotion recognition from physiological signals using time-frequency analysis methods. In: *2018 International Conference on Emerging Trends and Innovations in Engineering And Technological Research (ICETIETR), Ernakulam*, pp. 1–5 (2018)
34. Işık, Ü., Güven, A.: Classification of emotion from physiological signals via artificial intelligence techniques. In: *2019 Medical Technologies Congress (TIPTEKNO), Izmir, Turkey*, pp. 1–4 (2019)
35. Widanti, N., Sumanto, B., Rosa, P., Miftahudin, M.F.: Stress level detection using heart rate, blood pressure, and GSR and stress therapy by utilizing infrared. In: *2015 International Conference on Industrial Instrumentation and Control (ICIC), Pune*, pp. 275–279 (2015)
36. Al Jaafreh, M., Hamam, A., El Saddik, A.: A framework to analyze fatigue for haptic-based tactile internet applications. In: *2017 IEEE International Symposium on Haptic, Audio and Visual Environments and Games (HAVE), Abu Dhabi*, pp. 1–6 (2017)

37. Chen, L., et al.: A lightweight end-side user experience data collection system for quality evaluation of multimedia communications. *IEEE Access* **6**(1), 15408–15419 (2018)
38. Zhang, K., Chen, L., An, Y., et al.: A QoE test system for vehicular voice cloud services. *Mob. Netw. Appl.* (2020). <https://doi.org/10.1007/s11036-019-01415-3>